



ALKAFOAM

ALKAFOAM is a high alkali product containing surfactants that is used in foam cleaning applications

- Effective soil removal properties for smoke house, oven, conveyors, trays, crates, bottle fillers, and production equipment.
- ALKAFOAM can also be used in cleaning heavily soiled floors
- Quickly removes fatty soils and carbon deposits.

General use instruction:

Foam Cleaning of processing area and equipment:

1. For better results, pre-wash surface with water to remove gross soil.
2. Prepare 1-5% solution of ALKAFOAM. Fill foamer equipment with water $\frac{3}{4}$ full to allow sufficient amount of air. Add approximately 1 – 2 liters of ALKAFOAM.
3. Add compressed air in the foaming equipment. Check pressure gauge if it reaches 35-45 psi before applying solution
4. Open release valve and start foaming making sure that the entire surface is covered with foam.
5. Allow contact time of 2-5 minutes.
6. Rinse thoroughly with water. (Do not allow foam to dry).

*For specific dilution or application, please consult Kalinisan Chemicals representative.

*Available in:

Carbouy, Drum

Proudly Manufactured by:

Kalinisan Chemicals Corporation
 Cainta, Rizal PHILIPPINES
 Tel: (02)682 -2873, 234-1204
www.kalinisanchemicals.com